

Three-Phase Transmission Line 579535 (8329-00)

FESTO

LabVolt Series

Datasheet



Table of Contents

General Description	2
Specifications	2

General Description

The Three-Phase Transmission Line consists of three iron-core inductors enclosed in a half-size EMS module. The inductors are specifically designed to simulate a high-voltage ac transmission line (typically 315 kV lines). The line impedance can be adjusted to four different values using a selector switch mounted on the front panel. A three-pole switch is used to induce transients by momentarily interrupting the power flow. Both sides (sender and receiver) of the Three-Phase Transmission Line are terminated on the front panel by 4 mm color-coded safety banana jacks.

Specifications

Parameter	Value
Ratings	
Line Reactance Settings	0, 60, 120, and 180 Ω
Nominal Line Current	1 A
Line Simulated Lengths	175, 350 and 525 km (109, 217 and 326 miles)
Physical Characteristics	
Dimensions (H x W x D)	154 x 287 x 440 mm (6.1 x 11.3 x 17.3 in)
Net Weight	8.2 kg (18 lb)
Shipping Weight	9.8 kg (21.6 lb)

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2019. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3
73770 Denkendorf
Germany

P. +49(0)711/3467-0
F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West
Eatontown, NJ 07724
United States

P. +1-732-938-2000
F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone
Québec QC G2N 2K7
Canada

P. +1-418-849-1000
F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com